



Key facts

- Pink face paper
- Brown reverse side paper
- Available in tapered and square edge
- Complies with EN 520 – Type F Thermal
- Conductivity 0.24W/mK

Marketing description

ISOVER PREMIUM 33 is 60% more hardwearing than standard plaster providing excellent resistance to glancing impacts or accidental damage such as scratching, gouging or chipping. Ideal for high-traffic areas including corridors, stairwells and canteens in healthcare, leisure, social housing, education or office buildings, as well as busy hallways and rooms in houses.

ThistlePro DuraFinish plaster can be used on plasterboard or undercoat plasters, or for re-plastering and repair work on previously finished walls.

Any damage to small areas does not spread or cause debonding, making repairs easier.

ThistlePro DuraFinish plaster is 60% more hardwearing than standard plaster providing excellent resistance to glancing impacts or accidental damage such as scratching, gouging or chipping. Ideal for high-traffic areas including corridors, stairwells and canteens in healthcare, leisure, social housing, education or office buildings, as well as busy hallways and rooms in houses.

ThistlePro DuraFinish plaster can be used on plasterboard or undercoat plasters, or for re-plastering and repair work on previously finished walls.

Any damage to small areas does not spread or cause debonding, making repairs easier.

Packaging

Technical Characteristic

| Category | Attribute | Value |
|-----------------------|---------------------------------------|--|
| Category Dimension | Attribute Number of plates per facing | Value 2 |
| | Attribute Number of layers | Value 5 |
| | Attribute Total thickness | Value 140 - max 3,9 |
| | Attribute Superficial Hardness | Value HD |
| Category General | Attribute Name | Value Isover Premium 33 |
| | Attribute Partition type | Value Separative Standard |
| | Attribute Insulate type | Value Glass wool |
| | Attribute Activ'Air | Value No |
| Category Performances | Attribute Fire Protection | Value 60 |
| | Attribute Acoustic attenuation | Value A2 - S1, d0 |
| | Attribute Sound Power Level | Value 120 |
| | Attribute Sound Absorption | Value RE CSTB AC14 63993720/2 Value RS 15-036 |



[Leer más](#)

Edited on 25.05.2020

Isover Premium 35

www.saint-gobain.com.mx

