

## Key facts

- Pink face paper
- Brown reverse side paper
- Available in tapered and square edge
- Complies with EN 520 – Type F Thermal
- Conductivity 0.24W/mK

## Marketing description

ThistlePro DuraFinish plaster is 60% more hardwearing than standard plaster providing excellent resistance to glancing impacts or accidental damage such as scratching, gouging or chipping. Ideal for high-traffic areas including corridors, stairwells and canteens in healthcare, leisure, social housing, education or office buildings, as well as busy hallways and rooms in houses.

ThistlePro DuraFinish plaster can be used on plasterboard or undercoat plasters, or for re-plastering and repair work on previously finished walls.

Any damage to small areas does not spread or cause debonding, making repairs easier.

## Characteristic

Category	Attribute	Value
Category Dimension	Attribute Number of plates per facing	Value 3
	Attribute Number of layers	Value 5
	Attribute Total thickness	Value 140
	Attribute Superficial Hardness	Value HD
Category General	Attribute Name	Value GypWall RAPID dB Plus
	Attribute Partition type	Value Separative standard
	Attribute Insulate type	Value Glass wool
	Attribute Activ'Air	Value No
Category Performances	Attribute Fire Protection	Value 60
	Attribute Acoustic attenuation	Value A2-S1, d0
	Attribute Classification of wet rooms	Value EA, EB
	Attribute Shock Proof	Value 120
Category References	Attribute n° PV acoustic	Value RE CSTB AC14- 4958201484/2
	Attribute n°PV fire	Value RS 15-036

## Product quantities

<b>Product</b>	<b>Coverage Qty</b>	<b>Coverage unit</b>
Isover Premium 33 15		1
Product vetrotech 10		2
Product PAM 5		3

---

Edited on 28.10.2020

System Spec Rigips

[www.saint-gobain.com.mx](http://www.saint-gobain.com.mx)

