

# System Specifications datasheet

---

## Key facts

- Pink face paper
- Brown reverse side paper
- Available in tapered and square edge
- Complies with EN 520 - Type F Thermal
- Conductivity 0.24W/mK

## Marketing description

ThistlePro DuraFinish plaster is 60% more hardwearing than standard plaster providing excellent resistance to glancing impacts or accidental damage such as scratching, gouging or chipping. Ideal for high-traffic areas including corridors, stairwells and canteens in healthcare, leisure, social housing, education or office buildings, as well as busy hallways and rooms in houses.

ThistlePro DuraFinish plaster can be used on plasterboard or undercoat plasters, or for re-plastering and repair work on previously finished walls.

Any damage to small areas does not spread or cause debonding, making repairs easier.

## Characteristic

### Dimension

Number of plates per facing

**3**

Number of layers

**5**

Total thickness

**140**

Superficial Hardness

**HD**

### General

Name

**GypWall RAPID dB Plus**

Partition type

**Separative standard**

Insulate type

**Glass wool**

Activ'Air

**No**

**Performances**

Fire Protection

**60**

Acoustic attenuation

**A2-S1, d0**

Classification of wet rooms

**EA, EB**

Shock Proof

**120**

**References**

n° PV acoustic

**RE CSTB AC14- 4958201484/2**

n°PV fire

**RS 15-036**

**Product quantities**

Product	Coverage Qty	Coverage unit
Isover Premium 33	15	1
Product vetrotech	10	2
Product PAM	5	3